



ROGUE VALLEY
Door
Wood Entrance Door
Clear IG
RVD-M-3*

Energy Performance Ratings

Product Description** Default Frame Wood	U-Factor/Solar Heat Gain Coefficient (SHGC)			
	Individual Option Number			
	¼ Lite ≤410†	½ Lite ≤900†	¾ Lite ≤1100†	Full Lite >1100†
2/SS/NA/AIR/0.374 Full Lite	0.44 0.11	0.43 0.20	0.43 0.26	0.43 0.34
	02426-00001	02456-00001	02486-00001	02516-00001
2/OF/NA/AIR/0.374 Full Lite	0.44 0.11	0.43 0.20	0.43 0.26	0.42 0.34
	02971-00001	03035-00001	03099-00001	03163-00001
2/SS/NA/AIR/0.374 True Divided Lite	0.45 0.10	0.44 0.17	0.44 0.22	0.44 0.29
	02427-00001	02457-00001	02487-00001	02517-00001
2/OF/NA/AIR/0.374 True Divided Lite	0.44 0.10	0.43 0.17	0.43 0.22	0.43 0.29
	02974-00001	03038-00001	03102-00001	03166-00001
Air Leakage	≤0.3 cfm.ft ²			

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturers literature for other product performance information.

* Numbers below the performance ratings are referenced in the NFRC Certified Products Directory. (e.g. RVD-A-1-01174-00001)

** Door components specific to this product.

*** per NFRC 100

† square inches

www.nfrc.org