



1-3/8 One-Lite Wood Sidelite

123 N.E. Beacon Drive
Grants Pass, OR 97526
www.roguevalleydoor.com

ENERGY Performance

- Energy savings will depend on your specific climate, house and lifestyle.
- For additional information visit NFRC's web site at www.nfrc.org.

U-Factor/Solar Heat Gain Coefficient (SHGC)

Product Description*	Glazing Description			
	1/4 Glass < 65	1/2 Glass < 350	3/4 Glass < 460	Full Lite > 460
2/A1/na/AIR/.375	.52 / .06	.51 / .19	.51 / .25	.51 / .33
2/A1/.20(2)/AIR/.375	.52 / .05	.49 / .16	.48 / .22	.47 / .28
2/SS/.20(2)/AIR/.375	.52 / .06	.51 / .19	.50 / .25	.50 / .33
2/A1/.04(2)/AIR/.375	.52 / .04	.48 / .11	.47 / .14	.45 / .18
2/SS/.04(2)/AIR/.375	.51 / .04	.48 / .11	.46 / .14	.45 / .18
Wood Stile & Rail	U-Factor = .52 SHGC = .02			

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size.

* # glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width

