



Multi-Lite Entrance Door

123 N.E. Beacon Drive
 Grants Pass, OR 97526
 www.roguevalleydoor.com

ENERGY Performance

- Energy savings will depend on your specific climate, house and lifestyle.
- For additional information visit NFRC's web site at www.nfrc.org.

U-Factor/Solar Heat Gain Coefficient (SHGC)

Product Description* Default Frame	Glazing Description							
	1/4 Glass		1/2 Glass		3/4 Glass		Full Lite	
2/S1/na/AIR/.375	.43	.15	.45	.25	.45	.29	.47	.34
2/A1/.20(2)/AIR/.375	.42	.14	.44	.22	.44	.25	.45	.30
2/S4/.20(2)/AIR/.375	.42	.14	.43	.22	.43	.25	.43	.30
2/A1/.20(2)/ARG/.375	.42	.14	.43	.22	.43	.25	.43	.30
2/S4/.20(2)/ARG/.375	.41	.14	.42	.22	.41	.25	.41	.30
2/S1/.04(2)/ARG/.375	.40	.11	.39	.16	.38	.18	.38	.21
Wood Stile & Rail	U-Factor = .41 SHGC = .07							

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size.

* # glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width

